



SE Controls and ALUK have tested the following profiles and are able to certify them



ALUK GB 58BW

FRAME REF NO.	OPENING VENT REF NO.
AW604	AW618 / AW620
AW605	AW618 / AW620
AW608	AW618 / AW620
AW625	AW618 / AW620
AW632	AW618 / AW620
AW634	AW618 / AW620
AW635	AW618 / AW620
U44008 (Hi)	U44103 / U44104 / U44105 (Hi)
U44009 (Hi)	U44103 / U44104 / U44105 (Hi)
U44012 (Hi)	U44103 / U44104 / U44105 (Hi)
U44018 (Hi)	U44103 / U44104 / U44105 (Hi)
U44045 (Hi)	U44103 / U44104 / U44105 (Hi)
U44047 (Hi)	U44103 / U44104 / U44105 (Hi)
U44048 (Hi)	U44103 / U44104 / U44105 (Hi)
U44053 (Hi)	U44103 / U44104 / U44105 (Hi)
U44055 (Hi)	U44103 / U44104 / U44105 (Hi)
U44056 (Hi)	U44103 / U44104 / U44105 (Hi)

ALUK GB 58BW System Parameters

ORIENTATION	MAX WEIGHT
TOP / BOTTOM / SIDE HUNG - 2 HINGES	45KG
TOP / BOTTOM / SIDE HUNG - 3 HINGES	67.5KG
TOP / BOTTOM / SIDE HUNG - 4 HINGES	90KG



ALUK GB 77IWE

FRAME REF NO.	OPENING VENT REF NO.
K5000	K5059
K2000 / U43630	K5059

ALUK GB 77IWE System Parameters

ORIENTATION	MAX WEIGHT
TOP HUNG	180KG
SIDE HUNG	55KG



ALUK GB SL52

FRAME REF NO.	OPENING VENT REF NO.
P-53-100	P-53-200

ALUK GB SL52 System Parameters

ORIENTATION	MAX WEIGHT
TOP HUNG	180KG
SIDE HUNG	55KG

The Tested Solutions document will be uploaded shortly. Please contact the team at facade@secontrols.com or call 01543 443060